



PISTON COMPRESSOR

From 6 litres 2 HP

To 500 litres 10 HP

TECHNOLOGY YOU CAN TRUST



Silenced Compressor

Silenced piston compressors are the perfect choice for indoor installation.

Thanks to their low residual noise level, they can be installed near the workplace which reduces the length of pipeworks and related pressure drop.

Fonolife

- Vertical design for small footprint
- Easy access to components
- Oil sight glass visible through the canopy
- Low rotation speed for reliability
- Control panel with hourmeter and power switch



TECHNICAL DATA

TYPE	H		Pressure		Flow		Power		rpm	V/Hz/Ph	dB(A)	Dimensions (mm)			Kg
	litre	bar	psi	l/min	cfm	HP	KW	L				W	H		
S4	-	10	145	462	16,3	4	3	1.120	400/50/3	64	815	520	915	100	
S5,5	-	10	145	577	20,4	5,5	4	1.375	400/50/3	64	815	520	915	100	
S5,5X	-	10	145	577	20,4	5,5	4	1.375	400/50/3	64	815	520	915	100	
S7,5X	-	10	145	701	24,7	7,5	5,5	965	400/50/3	64	880	590	1.200	170	
S10X	-	10	145	923	32,6	10	7,5	860	400/50/3	64	880	590	1.200	170	

X= Star delta starter version

Fonocompact Pro

FONOCOMPACT PRO range includes the same benefits as the BELTAIR PRO range, ensuring limited noise emission thanks to an insulating canopy that includes a control panel with hourmeter and enables easy service access.



Floor mounted



Floor mounted with tank inside (27L)



Stationary on tank











Stationary with dryer on tank

Fonocompact Pro



Floor Mounted









Some installations are already fitted with an air vessel. In that case, a floor mounted unit can be the alternative.

TECHNICAL DATA															
TYPE											dB(A)				
	litre	bar	psi	l/min	cfm	HP	kW	rpm	V/Hz/Ph	L		W	H	Kg	
F4SPRO	-	11	159	514	18,1	4	3	1.450	400/50/3	68	820	635	795	143	
F5,5SPRO	-	11	159	653	23,1	5,5	4	1.370	400/50/3	68	820	635	795	150	
F7,5SPRO	-	12	174	827	29,2	7,5	5,5	1.400	400/50/3	68	1.230	760	875	229	
F10SPRO	-	12	174	1.210	42,7	10	7,5	1.300	400/50/3	68	1.230	760	875	248	

(*) Star delta models available from 5,5 HP (+6 kg)









Floor Mounted with Tank Inside

With less than 0,35 m², our units will provide compressed air and storage capability as well as ensuring a low noise level for easy installation.

TECHNICAL DATA															
TYPE											dB(A)				
	litre	bar	psi	l/min	cfm	HP	kW	rpm	V/Hz/Ph	L		W	H	Kg	
27F2MSPRO	27	8	116	254	9	2	1,5	1.250	230/50/1	64	760	430	845	80	
27F2SPRO	27	8	116	254	9	2	1,5	1.250	400/50/3	64	760	430	845	80	
27F3MSPRO	27	8	116	320	11,3	3	2,2	1.570	230/50/1	65	760	430	845	81	
27F3SPRO	27	8	116	320	11,3	3	2,2	1.570	400/50/3	65	760	430	845	81	

Stationary Models On Tank

User friendly model including air tank from 270 up to 500 litres for a footprint of 0,95 or 1,45 m², this unit offers you a workplace solution thanks to a low noise level.

TECHNICAL DATA															
TYPE											dB(A)				
	litre	bar	psi	l/min	cfm	HP	kW	rpm	V/Hz/Ph	L		W	H	Kg	
270F4SPRO	270	11	159	514	18,1	4	3	1.450	400/50/3	68	1.470	635	1.360	213	
270F5,5SPRO	270	11	159	653	23,1	5,5	4	1.370	400/50/3	68	1.470	635	1.360	220	
500F5,5SPRO	500	11	159	653	23,1	5,5	4	1.370	400/50/3	68	1.900	635	1.480	267	
500F7,5SPRO	500	11	159	827	29,2	7,5	5,5	1.400	400/50/3	68	1.900	760	1.520	369	
500F10SPRO	500	11	159	1.210	42,7	10	7,5	1.300	400/50/3	68	1.900	760	1.520	388	









(*) Star delta models available from 5,5 HP (+5 kg)

- wheelset and handle kit available as an option for 270 litres models

Stationary Models With Dryer On Tank

This model is a complete workplace air center including tank and selected fridge dryer of our range to insure production of dry compressed air with minimum footprint and low noise level.

All connections are done in factory for easy installation and reduced pressure drop.

TECHNICAL DATA															
TYPE											dB(A)				
	litre	bar	psi	l/min	cfm	HP	kW	rpm	V/Hz/Ph	L		W	H	Kg	
500F5,5SEPRO	500	11	159	653	23,1	5,5	4	1.370	400/50/3	68	1.900	635	1.480	297	
500F7,5SEPRO	500	11	159	827	29,2	7,5	5,5	1.400	400/50/3	68	1.900	760	1.520	399	
500F10SEPRO	500	11	159	1.210	42,7	10	7,5	1.300	400/50/3	68	1.900	760	1.520	418	

(*) Star delta models available from 5,5 HP (+6 kg) - Dryer power supply: 230/50/1

All products manufactured by CECCATO ARIA COMPRESSA S.p.A. are designed and produced in conformity with current European directives.

98/37/CEE
MACHINERY DIRECTIVE

89/336/ CEE EMC
DIRECTIVE

73/23/ CEE
LOW TENSION DIR.

97/23/CEE
PED DIRECTIVE

87/404 - 90/488
93/68/CEE
SIMPLE PRESS. VESSELS DIR.

The manufacturer reserves the right to make any change to the products in order to improve.



Design
Manufacture, Sales and
Service of air compressors,
air dryers and air filter



KOMPRESOR SERVIS
Hrvatskoselska 14
10250 Lucko - Zagreb
tel:6530-577 fax:6547-917
www.kompresor.hr
damir.zutic@kompresor.hr